



Diamond Pro®

Professional Groundskeeping Products

PRODUCT: Diamond Pro Calcined Clay Drying Agent.

MANUFACTURER: OIL Dri Corporation of America.

PRODUCT DESCRIPTION: Natural mineral with a blend of Montmorillinite, illite, and amorphous silica. 40% minimum & 60% minimum amorphous silica. Material must be processed via rotary kiln operation at temperatures above 1200 degrees Fahrenheit. Material must be screened and de-dusted.

INSTALLATION: Apply evenly in wet areas 1- 50# bag at a time to dry area and stabilize footing. Lightly rake Rapid Dry into wet area after leveling with rake or drag mat. Rapid Dry should remain on field after water is absorbed.

STABILITY: Degradation not to be over 5% utilizing ASTM-C88 Sulfate Soundness Test and Static Degradation Test.

CHEMICAL DESCRIPTION:

Si O ₂	74%
Al ₂ O ₃	11%
Fe ₂ O ₃	5%

All other chemicals equal less than 5% and include traces CaO, MgO, K₂O, Na₂O, and TiO₂.

BULK DENSITY: 34 to 36 lbs per cubic feet

COLOR: Reddish/Brown

FREE MOISTURE: 0.7%

Ph: 5.5% to 7%

SIEVE ANALYSIS:

+12	0.1%	-60 to + 100	0.2%
-12 to +16	99.3%	-100	0.1%
-16 to +80	0.1%		
-80 to +100	0.3%		